

# ACCESSORIES

## VALVES



check valve

VNR 1

VNR 1 1/4

VNR 1 1/2

VNR 2

foot valve

VDF 1

VDF 1 1/4

VDF 1 1/2

VDF 2

## PRESSURE GAUGES



axial connection type

MA 0-6

MA 0-6 ABS

radial connection type

MR 0-10

MR 0-12

MR 0-16

## CONNECTOR



type

connection

RA5 H 92

G 1

RA5 H 105

G 1

## PRESSURE SWITCHES



type

standard setting

max pressure

FSG 2

1,4 - 2,8 bar

4,5 bar

FYG 22

5,4 - 7 bar

7 bar

FYG 32

8 - 10,5 bar

10,5 bar

## SPHERICAL VESSEL



type

connect.

capacity

SS 24

G 1

24 l

BUTYL rubber diaphragm.

## CYLINDRICAL VESSEL



vessel with base and feet

type

connect.

capacity

SC 20 BP

G 1

20 l

BUTYL rubber diaphragm.

## INOX CYLINDRICAL VESSEL



vertical cylindrical vessel

type

connect.

capacity

SCX 20

G 1

20 l

BUTYL rubber diaphragm.

## INOX CYLINDRICAL VESSEL



vessel with base and feet

type

connect.

capacity

SCX 20 BP

G 1

20 l

BUTYL rubber diaphragm.